




ORION

DUO

Double your performance



UV anti-fraud
solution available

Seac Banche Orion is designed to simplify the processing of cheques and other documents at the point of presentation.

This unique reader scanner is the logical development to provide functionality and performance normally found in devices too big for modern teller positions in a unit with the same footprint of a check reader. A wide range of options - including colour imaging, voiding/endorsing functionalities and card management - further enhance its flexibility and broaden its scope of use.

Orion Duo

Despite its compact size, **Orion Duo** has the capability to process a large volume of documents and therefore addresses the needs of a large range of desktop applications.

Like the other members of the **Orion Team** its design and elegance it will beat home in any environment. As the name suggests **Orion Duo** has two output stacking pockets. Sorting of checks and vouchers can be under program control or by operator decision. You can decide which sorting method is right for your needs.

Orion Duo symbolises the team aspect of **Orion**, having the innovative technology, elegance, optional devices and functionality of the Classic and HRP models including the graphic printer and adding the Dual output pockets.

- Key specification:
- Autofeeder with a capacity up to 100 documents
- Dual output pockets, capacity 100 +100 docs
- AGP printer 300 dpi

PAPER HANDLING

Autofeeder with a capacity of up to 100 documents
90 gr/sq
Double feed control
Output stacker: capacity approx. 100 documents
90 gr/sq
Transport speed: 560 mm (22")/sec

THROUGHPUT OPTIONS

Drop feed, 65 dpm, 130 dpm

DOCUMENT SPECIFICATIONS

Width: 70 to 225 mm (2.76" to 8.86")
Height: 52 to 106 mm (2.05" to 4.17")
Weight: 60 to 120 g/sqm (18.7 to 32 lbs)

CODELINE READING

MICR: magnetic fonts CMC7 and E13B
OCR (optional): optical fonts OCR-A, OCR-B, OCR A-B, OCR alphanumeric, E13B
Barcode reading (optional)
Additional deco capabilities (2D barcode, multiple snippets - optional)

IMAGE CAPTURE

Front and rear images in one pass (duplex)
Imaging available
300 x 300 dpi or 254 x 254 dpi or 200 x 200 dpi or 100 x 100 dpi
Higher resolution available for 2D barcode decoding
256 or 16 grey levels or colour 64K (optional)

IMAGE FORMAT

Bitmap, Jpeg, Tiff, G4 (B/W)

INTERFACE

USB 2.0
RS-232 (codeline reader emulation)

API SOFTWARE TOOLS



Designed for MS Windows XP
Available for MS Windows 2000, 95/98/ME
Vista

DIMENSIONS

Length: 320 mm (12,6")
Width: 170 mm (6.3")
Height: 180 mm (7.1")
Weight: 2 Kg (4,41 lbs)

COMPONENT

Antifraud feature by UV light
Watermarking feature on jpg image

Rear Inkjet Printer

Programmable endorser, application controlled
High-capacity cartridge, 4-lines, 300 x 300 dpi or 1-line 96 x 96 dpi
Line of data can extend to full width of document

Front Stamp (optional)

Self-inking cancellation stamp
Max. dimensions: 22 x 16 mm (0.6 x 0.9")

Magnetic badge reader (optional)

Manual swipe reader Tracks 1&2 or 2&3

Chip memory card (optional)

"Dip" reader/writer integrated in the reader scanner (Not available)

Duty Cycle

Daily Duty Cycle 3000 documents
Life Cycle 2 millions document



SEAC BANCHE S.p.A. Headquarters
Via dell'Albereto, 69 - 50041 Calenzano (FI), Italy
Tel: +39 055.8870700 - Fax: +39 055.8873646
Email: info@seacbanche.com - Website: www.seacbanche.com