



The Seac Banche RDS 3000 is suitable for data capture and document imaging requirements based on checks and checksized financial documents such as credit transfer slips, travellers cheques, utility bills and other vouchers.

Our continuous technology update allows better throughput - up to 65 documents per minute on the basic unit and near 100 on the new high-speed version RDS 3500 - and raises the performance of this successful product to even higher standards of excellence. While the RDS 3000 and 3500 capture high-quality images in greyscale, the enhanced version RDS 6000 allows front and back scanning in full-colour in a single pass, providing equally accurate codeline reading.

MODELS

RDS 3000: greyscale imaging, standard speed RDS 3500: greyscale imaging, high speed RDS 6000: colour or greyscale imaging, standard speed

PAPER HANDLING

Automatic document feeder with a capacity of up to 80 documents

Double feed control (IR standard, Ultrasound optional)

Two output stackers: capacity approx.

50 documents each

Transport speed (standard): 480 mm (18.9")/sec up to 70 dpm

High speed (RDS 3500 only): 866 mm (34")/sec up to 100 dpm

IMAGE CAPTURE

Greyscale:

RDS 3000: up to 3 images in one pass (front, rear, front with red dropout) at standard speed. Multiple output format one pass

RDS 3500: front & rear images in one pass at high speed, Multiple output format one pass 200 x 200 dpi or 100 x 100 dpi

Higher resolution up to 200 x 254 dpi or 100 x 127 dpi available by reducing the track speed (MICR reading not supported)

256 or 16 grey levels

Colour:

RDS 6000: front & rear colour images in one pass. Multiple output format one pass Colour depth 16-bit (64k colours) Greyscale and black & white imaging remains available

IMAGE FORMAT Bitmap, Jpeg, Tiff, G4 (B/W)

CODELINE READING

alfanumeric, E13B

DOCUMENT SPECIFICATIONS

Width: 100 to 225 mm (3.94" to 8.86")

Height: 52 to 108 mm (2.05" to 4.09")

Weight: 60 to 120 g/sqm (16 to 32 lbs)

MICR: magnetic fonts CMC7 and E13B

INTERFACE

USB 2.0

API SOFTWARE TOOLS



Designed for MS Windows XP Available for MS Windows 2000,95/98/ME Vista compatible

OCR (optional): optical fonts OCR-A alfanumeric, OCR-B

Barcode (optional): Interleaved 2 of 5, Code 39, Code

DIMENSIONS

Length: 330 mm (13.0") Width: 165 mm (6.5") Height: 185 mm (7.3") Weight: 5.8 Kg (12.8 lbs)

ADDITIONAL FEATURES

Rear Inkjet Printer


Programmable endorser, application controlled Line of data can extend to full width of document Adjustable at 2 different heights

Front Stamp (optional)

Roll-on cancellation stamp with inking roller Maximum dimensions: 34.3 x 18.5 mm (1.4 x 0.7") Not available on RDS 3500 model.

Magnetic Badge Reader (optional)

Manual swipe reader Tracks 2&3 or 1&2



Via dell'Albereto, 69 - 50041 Calenzano (FI), Italy Tel: +39 055.8870700 - Fax: +39 055.8873646 Email: info@seacbanche.com - Website: www.seacbanche.com

